

INTRODUCTION

T60 is an electric tow tractor with rated capacity of 6000kg. The compact design and excellent flexibility are suitable for any tight areas. Equipped with powerful batteries and the operation is stable and reliable.



T60N

NEW!

**Electric Sit-on TOW Tractor
with capacity of 6000kg**

ADVANTAGES

- Compact design and beautiful appearance
- Small turning radius
- Good mechanical performance and no pollution
- Low center of gravity, good stability when turning and driving
- Long service life
- Operating efficiency is high



Type sheet for industrial tractor acc. to VDI 2198 1KG-2.2LB 11INCH=25.4MM

Distinguishing mark	1.2	Manufacturer's type designation		T 60N	
	1.3	Power (battery ,diesel,petrol gas,manual)		Electric	
	1.4	Operator type		Seat	
	1.5	Load Capacity / rated load	Q(t)	6.0	
	1.7	Rated drawbar pull	F(N)	1500	
	1.8	Largest traction	F(N)	4500	
	1.9	Wheelbase	Y(mm)	1222	
	Weight	2.1	Service weight	kg	1500
	Wheel chassis	3.1	Tires		Rubber wheel
3.2		Tire size, front	$\phi \times w$ (mm)	6.50-10	
3.3		Tire size, rear	$\phi \times w$ (mm)	4.00-8	
3.5		Wheels, number front/rear(x=driven wheels)		2x/1	
3.6		Tread, front	b10(mm)	/	
3.7		Tread, rear	b11(mm)	893	
Tires, Chassis		4.9	Height of tiller in drive position min./ max.	h14 (mm)	1375
	4.19	Overall length	l1 (mm)	2020	
	4.21	Overall width	b1 (mm)	1140	
	4.32	Ground clearance, centre of wheelbase	m2 (mm)	135	
	4.35	Turning radius	Wa (mm)	1550	
Performance data	5.1	Travel speed, laden/ unladen	km/h	9.0/13	
	5.10	Service brake		Electromagnetic	
E- Motor	6.1	Drive motor rating S2 60min	kW	6.8	
	6.3	Battery acc. to DIN 43531/ 35/ 36 A, B, C, no		DIN	
	6.4	Battery voltage, nominal capacity K5	V/Ah	48/300	
	6.5	Battery weight	kg	AC-Speed contorl	
Addition data	8.1	Type of drive control		8.1	
	8.4	Sound level at driver's ear acc. to EN 12053	dB(A)	<70	

